

# sp-302 / sp-304 / sp-308

## 1x2 / 1x4 / 1x8 HDMI Splitters - Distributors Amplifiers 4K-2K with EDID Management

Our Splitters sp-302 (1x2 HDMI) / sp-304 (1x4 HDMI) / sp-308 (1x8 HDMI) provides the most cost effective and advanced HDMI splitter solution on the market, by which the high definition video and high quality audio can be transmitted to 2 different locations without losing quality. Also support all 3D formats and the true 4K-2K video.



### Features

- Supports HDMI Deep Color & 3D / DVI 1.0 compliant
- HDCP 1.3 compliant
- Wide frequency range: 25MHz~340MHz
- Video bandwidth: 10.2Gbps
- Resolution up to 4K2K @30
- Supports default EDID and has ability to learn the EDID of displays
- Supports Dolby Digital, DTS-HD and Dolby TrueHD audio
- Mini-USB firmware update for expanding compatibility

### Technical Specifications

Role of Use: Splitter - Distributor Amplifier

Supported Input & Output: HDMI

Video Bandwidth: Single-link 340MHz [10.2Gbps]

Video Support: Up to 4K2K @30

Audio Support: DTS-HD Master Audio, Dolby TrueHD Dolby Digital, DTS, DVD-Audio, LCPM, SACD, MCPCM

### MECHANICAL

Dimensions (LxWxH): Desktop - sp-302 [113x62x25mm] & sp-304 [154x83x25mm] & sp-308 [328x102x26mm]

Weight: 2.1 lbs [sp-308] / 1.1 lbs [sp-302 & sp-304]

Power Supply: 5V-2A DC

Power consumption: 10 Watts Max

Operation temperature: 0-40 C

Relative humidity: 20-90% RH

